

Low VOC

# Low VOC Spray Contact Adhesive

A red spray contact adhesive that is excellent for bonding Armaflex sheet and roll insulations to vessels, tanks, ducts and mechanical equipment



- Formulated for Armaflex Insulations
- Low VOC
- Saves installation time and labor
- Complies with SCAQMD Rule 1168
- Faster, easier, less mess

 armacell®



GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit [ul.com/gg](http://ul.com/gg).

## Technical Data: Low VOC Spray Contact Adhesive

### Description:

A red spray contact adhesive that is excellent for bonding Armaflex sheet and roll insulations to vessels, tanks, ducts and mechanical equipment

### Specifications Compliance:

SCAQMD rule 1168

### Approvals, Certifications, Compliances:

- GREENGUARD Gold Certified

### Typical Properties

Specifications:	Values
<b>Color:</b>	Red
<b>Net Weight:</b>	7.8 pounds per gallon (0.934 kg/l)
<b>Composition:</b>	Synthetic rubber base and solvents
<b>Volatile Organic Compounds (VOC) Content:</b>	2.2 g/l
<b>Solids Content</b>	Approximately 22% by weight.
<b>Coverage</b>	1600 square feet per canister maximum, single coat. Depending on porosity of materials bonded, spray pattern and air temperature
<b>Shelf Life</b>	1 year in original sealed container; storage temperature 60°F to 80°F (16°C to 27°C)
<b>Minimum Drying Time</b>	4-6 minutes under normal conditions
<b>Temperature Limits</b>	180°F (82°C)—Armaflex Pipe Insulation seams and joints
<b>Container Sizes</b>	Gross Weight 39 lbs. Net Weight 27 lbs. Aerosolized cannisters
<b>Application Temperature:</b>	Recommended between 60°F to 80°F (16°C to 27°C)

### ARMACELL LLC

TEL: 800.866.5638

FAX: 919.304.3847

info.us@armacell.com

www.armacell.us

7600 Oakwood Street Extension, Mebane, NC 27302



Armacell provides this information as a technical service. To the extent the information is derived from sources other than Armacell, Armacell is substantially, if not wholly, relying upon the other source(s) to provide accurate information. Information provided as a result of Armacell's own technical analysis and testing is accurate to the extent of our knowledge and ability, as of date of printing, using effective standardized methods and procedures. Each user of these products, or information, should perform their own tests to determine the safety, fitness and suitability of the products, or combination of products, for any foreseeable purposes, applications and uses by the user and by any third party to which the user may convey the products. Since Armacell cannot control the end use of this product, Armacell does not guarantee that the user will obtain the same results as published in this document. The data and information are provided as a technical service and are subject to change without notice.