

DP**88**

SPRAY EDGE COATING

DP 88 is an aerosol spray edge coating or "duct butter" designed to quickly and conveniently coat the edges of insulation. DP 88 combines the advantages of quick drying aerosol adhesives with the tack-free and flexible properties of sealants and liner adhesives.

Recommended Uses:

- Encapsulating cut edges, rips and tears in fiberglass insulation.
- May be used on internally lined ductwork and rigid fiberglass ductwork.

Features and Benefits:

- Convenient / Easy Application
- Tack-Free After Curing
- Quick Drying
- Encapsulates Cut / Damaged Fiberglass
- Flexible
- Durable
- CARB Compliant

Directions For Use:

Surface Preparation: Surfaces should be clean, dry and free of dirt, oil and any foreign matter.

Application: Use in well ventilated area. Shake can vigorously until ball rattles; continue shaking for 30 seconds before use. Always point spray tip away from yourself and others. For best performance, use this product at temperatures above 50°F. Hold spray can tip 3 to 8 inches from surface to be sprayed, always at a 90° angle to surface. Apply even coats, overlapping passes slightly to insure proper coverage. Keep can moving to avoid excessive build-up, puddling, or bubbles. Dries to touch in 3 to 5 minutes and fully cures in 30 minutes.

IMPORTANT: After use, invert can and spray until only gas comes out to clear valve and spray tip.

Clean Up: Mineral spirits

DANGER! EXTREMELY FLAMMABLE. Contents under pressure. Do not puncture or incinerate can, even when empty. Keep away from heat and flame. Do not spray near sparks, open flames, or other ignition sources. Store at temperatures below 120°F in an area away from direct sunlight. Do not discard can in garbage compactor. Always point spray tip away from yourself and others. Avoid breathing vapors or contact with eyes or skin. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Technical Data:

Color: Black

Chemical Family: Synthetic rubber

Application Temperature: 50°F - 110°F

Service Temperature: 0°F to 200°F

Flammability: Extremely Flammable

Dry Time: Dries to touch in 3 to 5 minutes depending on humidity, temperature, substrate, and application thickness. Fully cures in 30 minutes.

Coverage: Typical application will yield up to 400 lineal feet on 1 inch duct liner per can.

Packaging: Net wt. 14 oz. cans supplied 12 cans per case

Shelf Life: 1 Year

**KEEP OUT OF REACH OF CHILDREN
CONSULT S.D.S. BEFORE USING**

NOTICE TO PURCHASER: No warranties, expressed or implied are made including merchantability and/or fitness for a particular purpose. Under no circumstances shall DESIGN POLYMERICS be liable for any loss or damage arising from the purchase, use, or inability to use this product, or for any special, indirect, incidental, or consequential damages. The user may send a sample of the product to DESIGN POLYMERICS for testing. If such testing proves a product defect, the user's sole and exclusive remedy is either reimbursement of the purchase price of the product or replacement of the product. No fabricator, installer, dealer, agent, or employee of DESIGN POLYMERICS has the authority to modify the obligations or limitations of this warranty. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state; therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of a product.



3301 W. Segerstrom
Santa Ana, CA 92704
Toll Free 800.641.0808
Phone 714.432.0600
Fax 714.432.0660
www.designpoly.com