DUCTMATE

# PROGUARD





# **Protective Duct Covering Solutions**

## Heavy Duty Grade and Standard Grade Plastic Film

- Dual-ply and single-ply polyethylene film
- High-tack and low-tack adhesive coating
- Elongation up to 600%

- Leaves no sticky residue on ductwork after removal
- Excellent strength
- Convenient pliability





### **Heavy Duty Grade and Standard Grade Plastic Film Duct Cover**

#### DESCRIPTION

ProGuard Heavy Duty is a dual-ply polyethylene film with a high-tack adhesive coating. It is specially-formulated to keep film attached and leave no residue when removed. Its unique manufacturing process gives ProGuard Heavy Duty unmatched puncture resistance, strength, elongation, and workability.

ProGuard Standard Grade is an economical singly-ply film with a low-tack adhesive coating.

#### BASIC USE

ProGuard is designed to be placed over the opening of the ductwork during storage and transportation to protect the inside of ductwork from dust, dirt and other particles that can lead to poor indoor air quality.

#### SPECIAL CHARACTERISTICS

- Heavy-Duty grade for superior performance
- Standard grade for light applications
- High-tack and low-tack adhesive coating
- Leaves no sticky residue on ductwork Elongation up to 600%
- Excellent strength with convenient pliability


#### PACKAGING INFORMATION

Item #	Grade	Dimension	Packaging
Color - Blue			
PG24B	Standard	24" x 200'	6 rolls/box
PG24BR	Standard Reverse Wound	24" x 200'	6 rolls/box
PG24B-2M	Standard 2 Mil	24" x 200'	6 rolls/box
PG36B	Standard	36" x 200'	6 rolls/box
PG36BR	Standard Reverse Wound	36" x 200'	6 rolls/box
PG36B-2M	Standard 2 Mil	36" x 200'	6 rolls/box
PG48B	Standard	48" x 200'	6 rolls/box
PG48B-2M	Standard 2 Mil	48" x 200'	6 rolls/box
PG60B-2M	Standard 2 Mil	60" x 200'	Special Order - Not Stocked
Color - Clear			
PG24	Heavy Duty	24" x 200'	1 roll/box
PG24-2M	Standard 2 Mil	24" x 200'	6 rolls/box
PG24K	Heavy Duty	24" x 1000'	1 roll/box
PG24C	Standard	24" x 200'	6 rolls/box
PG36	Heavy Duty	36" x 200'	1 roll/box
PG36-2M	Standard 2 Mil	36" x 200'	6 rolls/box
PG36K	Heavy Duty	36" x 1000'	1 roll/box
PG36C	Standard	36" x 200'	6 rolls/box
PG48	Heavy Duty	48" x 200'	1 roll/box
PG48C	Standard	48" x 200'	6 rolls/box

#### DIRECTIONS FOR USE

Before applying ProGuard, the duct surface should be clean, dry, and free of any dirt, oil, grease, water, or foreign matter.

Allow any duct sealant to cure fully before encapsulating duct ends with ProGuard, as with any duct cover product. You may set the duct upright on a pallet and encapsulate just the top, allowing air to flow through the bottom until the sealant has cured.



#### TECHNICAL INFORMATION

Color: Blue and Clear

Adhesion: Adheres to Galvanized, Stainless Steel,

Galvannealed, Aluminum, PVC Coated, Aluminized, and Black Iron.

Polyethylene

**Shelf Life:** For best results use within 1 year of purchase

Elongation: Heavy Duty Grade: 600%

Standard Grade: 325%

**Break Strength:** Heavy Duty Grade: 13.1 lbs/in (5.9 kg/mm)

Standard Grade: 12.6 lbs/in (5.7 kg/mm)

Indoor/Outdoor: Stands up to the rain, snow, or sun

**UV** Resistance: Good

Adhesive: Acrylic. Does not leave sticky residue on

ductwork after removal

**VOC Content:** 0 g/L

#### LIMITED PRODUCT WARRAN

Ductmate warrants that ProGuard, when properly installed and maintained, will be free from defects in material and workmanship, and will comply with all written specifications made by Ductmate at the time of sale. Ductmate's warranty shall run for a period of one year from the date

Type:

Warranty Limitation
The warranty stated above is in lieu of all other warranties, express or implied, including but not limited to the implied warranties of MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Although Ductmate may have suggested the product, or provided written or oral advice to the Purchaser, it is the Purchaser's responsibility to test and determine the suitability of ProGuard, for the intended use and purpose, and Purchaser and/or its customer assumes all risk and liability whatsoever regarding such suitability.

Limitation of Liability
In the event of a breach of the above warranty, Ductmate's sole obligation, and Purchaser's sole and exclusive remedy, shall be, at Ductmate's option, repair or replacement of any defective products, or refund of an applicable portion of the purchase price. Ductmate shall have no liability for costs of removal or reinstallation of the product. The Purchaser agrees that no other remedy, including but not limited to loss of profits, loss sales, injury to person or property, or any other special, incidental or consequential damages, shall be available to the Purchaser for any claim arising out of this Agreement, regardless of whether such claim is made in contract or in tort, including strict liability in tort. In no event will Ductmate be obligated to pay damages to the Purchaser in any amount exceeding the purchase price that the Purchaser paid to Ductmate for the allegedly defective product.



#### Charleroi. PA

210 Fifth Street Charleroi, PA 15022 724-258-0500 FAX: 724-258-5494

#### Lodi. CA

810 S. Cluff Avenue Lodi, CA 95240-9141 209-333-4680 FAX: 209-333-4678

www.sfiprogram.org This spec data is printed on paper that meets the Certified Fiber Sourcing requirements of the SFI program and contains 10% recycled content

#### Distributed By:





